

LED Switching Power Supply(C&V)

- Protections:short circuit/over load/over voltage/over temperature
- High power density, small size, high only 13.9mm,saving installation space;
- Design for indoor installations
- 100% full load burn-in test,
- Widely used in LED lighting and IT equipment
- Compliance to worldwide safety regulation for led lightings.



CB



CE

SELV


IP20




Specification

Model		100WHS-24	100WHS-48
OUTPUT	Output voltage	24VDC	48VDC
	Output voltage range	24VDC±2%	48VDC±2%
	Output current	Max 4.17A	Max 2.1A
	Output power	Max 100W	
	Output power range	0~100W	
	Linear Regulation	±1%	
	Load Regulation	±1%	
	Ripple & Noise	±2%	
	Start-up Time (Typ)	600ms/230VAC	
INPUT	Input voltage	176-264Vac	
	Frequency	50Hz/60Hz	
	Input current	1.1A Max.	
	Power factor	PF>0.55	
	No-load power consumption	< 0.5W	
	Efficiency (typ.)	91%	91%
	Inrush current(typ.)	Cold start 60A at 230Vac	
	Control surge capability	L,N:1KV L,N-PE:2KV	
	Leakage current	Max. 0.5mA	
ENVIRONMENT	Working temperature	ta: -30°C~ 45°C tc: 90°C	
	Working humidity	20 ~ 99%RH, non-condensing	
	Storage temp., humidity	-40°C ~ 80°C, 10~95%RH	
PROTECTION	Overtemperature	Protection type: Turn off the output voltage, after the temperature drops, re-energize to restore.	
	Over voltage protection	Shut down the output when non-load voltage≥27-35V, re-power on to recover after fault condition is removed.	Shut down the output when non-load voltage≥52-63V, re-power on to recover after fault condition is removed.
	Over load protection	Shut down the output when current load ≥110%~150%, auto recovers.	
	Short circuit protection	Protection type: It can be automatically restored after the fault is eliminated.	
SAFETY & EMC	Withstand voltage	I/P-O/P:3750Vac	
	Isolation resistance	I/P-O/P: 100MΩ/500VDC/25°C/70%RH	
	Safety standards	IEC/EN61347-1, IEC/EN61347-2-13	
	EMC emission	EN55015, EN61000-3-2 Class C, IEC61000-3-3	
	EMC immunity	EN61000-4-2,3,4,5,6,8,11 EN61547	
Reliability and Quality Control	Impact aging	100% of the product is fully loaded and impacted for 4 hours under an environment of at least 40°C ± 5°C	
	Component derating	Under the steady-state conditions of rated input and output, the stress of components will not exceed its maximum nominal value	
NOTE	1. All parameters not specifically mentioned are measured at 230VAC input, rated load and 25°C ambient temperature. 2. Ensure that the power supply is used under the rated parameters and environment.		

Dimensions
Unit:mm




Relationship diagrams



Packaging Information

DIMENSION	135x33x13.9mm(LxWxH)
PACKING	mm(LxWxH)
CARTON QUANTITY	PCS
CARTON SIZE	mm(LxWxH)
WEIGHT	90g±10g/PCS



* No further notice if any changes in the manual. Product function depends on the goods. Please feel free to contact your supplier if any question.